

## Technical Data

### Rubber Wheel Stops

*The best parking solution to protect your car.*



#### Product description

**Manufactured** from recycled high-impact resistant rubber, Wheel stops are long lasting, durable, and cost-effective solutions. High intensity reflective tape increases visibility - especially at night, and provides the necessary guidance to drivers when parking in tight spots. Wheel stops not only help protect your parking structure, but also help protect your customers' vehicles from potential damage inside the parking area.

#### Recommended use

**Ideal** for surface and multi-level parking lots, factory / warehouse, and areas surrounding loading docks,

#### Standardized Size

Model	Size (LxWxH) mm	Spikes needed
PRO 180	<b>1800 X 150 X 100</b>	<b>4 Spikes (American Standard)</b>
PRO 165	<b>1650 X 150 X 100</b>	<b>3 Spikes (Australian Standard)</b>
PRO 120	<b>1200 X 150 X 100</b>	<b>2 Spikes</b>
PRO 90	<b>900 X 150 X 100</b>	<b>2 Spikes</b>

#### Features

- Molded reflective tape
- Lightweight, uniform units
- 100% recycled rubber from tires
- Engineered, durable construction design
- Superior construction ensures no warping, cracking, chipping or rotting
- Flexible, conforms to any road surface
- Resistant to UV, moisture, oil and extreme temperature variations



## Installation over Concrete surface

- Use 1/2" or 5/8 lag bolts (6" long).
- Drill 1/2" diameter pilot holes (3 - 4" in depth) through the product's installation holes.
- Remove the product; re-drill the holes for the diameter and depth required by the metal shields
- Install the metal shields, re-position the product and bolt with lag bolts and washers.

## Installation over asphalt surface

- Drill 1/2" diameter holes (75mm in depth) in the asphalt through the product's holes.
- Drive 1/2" rebar spike (350mm long) through the holes in the product.

---

## Storage

The product must be stored in accordance with national regulations. Storage conditions are to keep in a dry, cool, well ventilated space and away from source of heat.

---

## Handling

Handle using Hand Gloves and Safety Goggles.

---

## Health and safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. In case of contact eyes, immediately flush eyes with plenty of water for at least 15 minutes and get normal medical attention if irritation persists.

---

## DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product can be used under conditions beyond our control, we can only guarantee the quality of the product itself. We also reserve the right to change the given data without notice. Minor product variations may be implemented in order to comply with local requirements.

